

果汁/茶饮料全自动吹瓶机系列工程规格表  
HOT FILLING SERIES

		单位 unit	PW-CS2000H	PW-C3000H	PW-CS2000H	PW-C4000H	PW-CS4000H	PW-CSS6000H	PW-CS6000H	PW-CS6000HE
成型组规格 MOLDING	合模力 Clamping force	kg	32000	48000	16000	64000	48000	48000	60000	60000
	模具行程 Clamping stroke	mm	160	160	110	160	140	120	140	140
	拉杆行程 Stretching stroke	mm	320	320	320	320	320	240	320	320
	底模行程 Bottom stroke	mm	60	50	80	50	50	50	50	50
	瓶子间距 Cavity pitch	mm	152.4	152.4	114.3	152.4	114.3	76.2	114.3	114.3
	模穴数 Number of cavity		2	3	2	4	4	6	6	6
	瓶型规格 CONTAINER	瓶子容量 Max container volume	ltr	3	3	1	2	1	0.45	1.5
颈部尺寸 Neck diameter range		mm	18-38	18-38	18-38	18-38	18-38	18-38	18-38	18-38
瓶身直径 Max container diameter		mm	130	130	90	130	90	60	90	90
瓶身高度 Max container height		mm	320	320	320	320	320	240	320	320
胚头数 Carriage unit		pcs	45	54	38	60	72	108	100	100
理论产能 THEORETICAL OUTPUT		bph	1000	1500	1000	2000	2000	3000	3000	3200
电力规格 ELECTRICAL SYSTEM	总耗电 Total power	KW	58	68	30	91	64	60	66	66
	加热功率 Heating power	KW	55	65	27	88	59	55	61	61
	灯管配置 Max. heating power	KW	78	92	38	125	84	68	87	87
空压规格 AIR SYSTEM	操作压力 Operating pressure	kg/cm <sup>2</sup>	7	7	7	7	7	7	7	7
	低耗电 Air consuming	ltr/min	2000	2000	1500	2000	2000	2000	2000	1500
	吹瓶压力 Blowing pressure	kg/cm <sup>2</sup>	35	35	35	35	35	35	35	35
	高压耗气量 Air consuming	ltr/min	7500	10000	5000	15000	10000	10000	14000	15000
冷冻机规格 CHILLED WATER	操作压力 Operation pressure	kg/cm <sup>2</sup>	3-4	3-4	3-4	3-4	3-4	3-4	3-4	3-4
	温度范围 Temperature	°C	130-140	130-140	130-140	130-140	130-140	130-140	130-150	130-150
	消耗量 Consuming	kcal/hr	10800	10800	5400	10800	10800	10800	16200	16200
	流量 Flow rate	ltr/min	160	160	60	160	160	160	240	240
冷却水规格 COOLING WATER	操作压力 Operation pressure	kg/cm <sup>2</sup>	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4
	温度范围 Temperature	°C	30	30	30	30	30	30	30	30
	消耗量 Consuming	kcal/hr	30000	45000	30000	45000	45000	45000	54000	54000
	流量 Flow rate	ltr/min	100	150	100	150	150	150	180	180
机台规格 MACHINE	机台尺寸(W*D*H) Machine size	mm	3500*2150*2500	4000*2150*2500	2400*2150*2500	5350*2150*2500	4000*2150*2500	4000*2150*2500	5350*2150*2500	5350*2150*2500
	机台重量 Machine weight	kg	3500	6500	2500	7000	6500	6500	7000	7000

备注

- REMARK
- 1、以生产0.6L瓶的基本耗气量。All data standard indication for 0.6L bottle.
  - 2、最终产能需依据瓶胚及瓶型而定。The actual output depends on the preform quality and bottle shape.
  - 3、规格有变更，恕不另行通知。Specifications are subject to change without notice.
  - 4、请提供稳定的环境温度。Please provide the stable temperature of air conditioner.